

# PRODUCT SPEC SHEET

## REMOVABLE FLUSH MOUNT AIR RETURN VENT, 6" x 6" (DRYWALL OPENING) CB5011



### FEATURES:

- Mud-in flush mount air return vent
- 2 magnetic tabs on vent cover for easy removal
- Primed vent cover ready to paint
- 24 gauge galvanized satin coat steel frame
- The vent cover is made from an impact resistant triple fibre reinforced cement board
- Made of non-flammable materials
- Moisture, mold, and water resistant
- Eco-friendly manufacturing and non-hazardous

### APPLICATION:

- Designed to be installed with 1/2" or 5/8" thick drywall.
- Steel frame screws onto the face of your drywall.
- For wall or ceiling installation.

### GENERAL SPECIFICATIONS:

|                               |                 |
|-------------------------------|-----------------|
| Vent Cover                    | 5.875" x 5.875" |
| Drywall Opening               | 6" x 6"         |
| Overall Dimensions with Frame | 8.375" x 8.375" |
| Depth                         | 0.487"          |
| Slotted Area                  | 3.75" x 3.75"   |
| Slot Size                     | 3.75" x 0.32"   |
| Number of Slots               | 6 Slots total   |
| Open Vented Area              | 6sq inches      |

### MATERIAL SPECIFICATIONS:

|                            |                                                                |
|----------------------------|----------------------------------------------------------------|
| Raw Materials              | Cement, fibres, quart sand, non hazardous fillers              |
| Density                    | $1.0 < D \leq 1.2 \text{ g/cm}^3$                              |
| Asbestos Content           | 100% asbestos-free                                             |
| Fire Resistance            | Non-combustible                                                |
| Water Absorption           | 40%                                                            |
| Resistant Bending Strength | 10.5 MPa dry                                                   |
| Moisture Movement          | 0.25%                                                          |
| Freeze Thaw                | No distortion after 25 repeated cycles of freezing and thawing |

