

Safe Use Instruction Sheet

The European Directive on Chemicals No. 1907/2006 (REACH) regulates the communication of information by Safety Data Sheets (SDS) for hazardous substances and mixtures. Our products made of continuous glass and polyester filaments or polyester staple fibres are considered ARTICLES and SDS's are not compulsory in terms of REACH regulation.

OSHA requires SDS's ONLY for materials that a) meet OSHA's definition of hazardous and b) are known to be present in the workplace in such a manner that employees may be exposed under normal conditions of use or in a foreseeable emergency. ADFORS's products pose no health or physical hazard and are classified as "Articles" as defined by OSHA. Based on these exemptions under the federal OSHA Hazard Communication Standard, an SDS is not required for ADFORS products.

Saint-Gobain ADFORS made a decision to deliver to our customers the appropriate information on safe handling and use of glass and polyester filament products through the **Safe Use Instruction Sheet**.

1 – COMPANY AND PRODUCT IDENTIFICATION

MANUFACTURER:

Head Quarters:

Saint-Gobain ADFORS
18, avenue d'Alsace
Les Miroirs – 92400 Courbevoie
☎ : +33 1 47 62 37 00

Production plants:

Saint-Gobain ADFORS Austria
Industriestr. II/7
A.7053 Hornstein
☎ + 43 2689 2234-0

Saint-Gobain ADFORS Spain
Pol. Ind. Bayas, 48-49-81-82
ES-09200 Miranda de Ebro
☎ + 34 947 34 74 04

Saint-Gobain ADFORS Cz,
Zahradni 256
CZ-67125 Hodonice
☎ + 420 515 207 111

Saint-Gobain ADFORS Cz
Sokolovská 106
CZ-57021 Litomysl
☎ + 420 461 651 111

Saint-Gobain Isover Benelux B.V.
Parallelweg 10
NL-4878 AH-Etten-Leur
☎ + 31 7650 80 000

Saint-Gobain America S.A. de C.V.
Prol. Zacatepec Manzana 42 Lote 3
Ciudad Industrial Xicohtencatl
MEX-Tetla, Tlaxcala CP 90431
☎ + 52 241 88 200

Saint-Gobain ADFORS Polska
Ul. Biecka 11
PL-38-300 Gorlice
☎ : +48 18 354 91 00

Saint-Gobain ADFORS America
14770 east avenue / P.O. box 390
14411-0390 ALBION
☎ +1 -(585) -589-4401

Saint-Gobain ADFORS Belgium
Kalkenstraat 86
9255 Buggenhout
☎ +32 52 39 93 70

Saint-Gobain ADFORS Germany
Rossauweg 14
93333 Neustadt an der Donau
☎ +49 9445/ 203-161

PRODUCT IDENTIFICATION:

“Woven and Non Woven Technical Fabrics”

COMMON NAMES:

Mesh fabrics (Vertex®)	Dry wall tapes (FibaTape®)
Insect screens (New York Wire®)	Wall coverings (Novelio®)
Glass loose fibre	Laid scrim
Glass veil	Coated glass veil
RECO fabrics	TECO fabrics
E-fabrics	TwinFab®
Cement Board reinforcement	
Glass reinforcement grid (GlasGrid®)	
Grinding Wheels (glass filament impregnated weaves for the abrasive industry)	
Cellulose or polyester laminate	
Coated Polyester Fabric	
Coated glass/polyester carded Web	
EDS (Extreme Dimensional Stability: Thermal and chemical bonded Polyester non-woven)	

2 – HAZARDS IDENTIFICATION

The products are composed of glass filaments and / or polyester and glass fibres reinforced with polyester and glass filaments.

The glass filaments are above 3µm in diameter, consequently not reach the lower respiratory tract and therefore have no possibility of causing serious pulmonary disease.

The products are **not classified as hazardous** according to European Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP) and its subsequent amendments.

This product is not considered to be or to contain hazardous chemicals based on evaluations made by our company under the Occupational Safety and Health Administration’s (OSHA) Hazard Communication Standard, 29 CFR 1910.1200.

Mechanical irritation (itching), eventually allergy (extremely rare), may be produced by dust generated on product processing. Under some conditions, the products may release Formaldehyde and other hazardous substances (see Chapter 3 COMPOSITION).

3 - COMPOSITION – INFORMATION ON CONSTITUENTS

Continuous filament glass products and Polyester fabrics or non-woven are articles in the meaning of REACH (1907/2006/EC).

These articles are composed of **E GLASS** or **C GLASS** in the form of continuous filaments and a **SIZE** with, in addition, a **BINDER** or **COATING** and / or **Polyester filaments**.

The CAS number of glass filaments is 65997-17-3 (corresponding to the oxides used for production).

E GLASS is a glass with a very low alkaline content.

C GLASS is a glass with very high alkaline content and low aluminium oxide content.

SIZE is a mixture of chemicals applied to the glass filaments in a maximum quantity of 2% - more generally between 0.5% and 1.5% by weight.

Most of this mixture is made up of basically non-reactive high molecular weight polymers, often natural ingredients (starches) with no reactive sites, which are not listed as substances in the EINECS nor ELINCS appendices.

In some cases, sizes are prepared from polymers with reactive sites or containing reactive monomers included in these lists. Most of the reactive sites are polymerised during the manufacturing process of E glass yarns.

A second type of ingredient (present in almost all sizes) is a member of the organo-silane family. These products account for less than 0,05% of the final weight of sized E glass. These products are included in lists of products requiring 'hazardous product' labelling in a pure state (for example in Europe R23/25 - H301/H331 toxic if swallowed or inhaled, R21 - H315 harmful in contact with the skin, R36 - H319 irritant for the eyes).

The manufacturer considers this risk as negligible as, although listed as dangerous products, the concentration is extremely low and they are polymerised during the production of E glass filaments.

Other products can be used in sizes often acting as lubricants. Usually the content is extremely low (under 0.1% of total weight) and as a general rule such products are not on the dangerous product lists or, as they have reacted, any possible risk has been reduced.

BINDERS in case of glass veils and **EDS** are water based phenol-formaldehyde (PF), melamine-formaldehyde (MF), urea-formaldehyde (UF), or polyvinyl, acrylic resins, Styrene Butadiene Rubber (SBR), other latex emulsions, starch, other bio sourced raw materials or blends of these binders. Their content in the glass veil is between 5 and 30 % by weight. Binders can contain black or yellow dyes.

No BINDER nor impregnation in case of Glass Loose Fibers and some **TECO Fabrics** (Greige fabrics, Caramelized fabrics)

COATING in case of glass veil are mineral based.

Calcium carbonate (CAS 1317-65-3) content < 80% by weight

Metal hydroxides (CAS1318-23-6 ; CAS 1309-42-8) content < 20% by weight.

COATING in case of grinding wheels are generally phenolic resins, and some polyurethane resins. Their content in the final product keeps the range 26 – 33 % by weight; in cases of certain products the content can reach 50 %.

COATING in case of wall covering, mesh, RECO/E-fabrics, laid scrims, roofing membranes and TwinFab are polyvinyl alcohol (laid scrim), ethyl vinyl acetate polymer (wall covering, RECO/E-fabrics), water dispersion of styrene-butadiene (mesh fabrics, TwinFab) coatings and polyvinyl acetate, ethyl vinyl acetate copolymer, ethylene-vinylchlorid copolymer, styrene-butadien copolymer, acrylic copolymer, aliphatic polyurethane (roofing membranes).

COATING in case of insect screens and Coated glass/polyester carded Web is PVC based coating with PVC plasticizer.

Polyvinyl Chloride (CAS 9002-86-2) content < 40 % by weight

Di-isonylphthalate (CAS 28553-12-0) content < 20 % by weight

COATING in case of glass reinforcement grid is Polymer binder-acrylic copolymer and Carbon Black

Carbon Black (CAS 1333-86-4) content <0.2% by weight

COATING in case of Cement Board is PVC based coating.

Alkanes, C14-17, chloro (CAS 85535-85-9) content <5% by weight

Solvent naphtha (petroleum), heavy arom (CAS 64742-94-5) content <2% by weight

Ethene, chloro-, homopolymer (CAS 9002-86-2) content <60% by weight

Diiso Decyl Phthalate (CAS 26761-40-0) content <18% by weight

Di(2-propylheptyl) phthalate (CAS 53306-54-0) content < 25% by weight

COATING in case of polyester reinforcement scrim is PVC based coating

Diisononylphthalat (CAS 28553-12-0) content < 25 % by weight

Hazardous substances potentially released from the products:

Product	Binder	Coating
Glass veils	Formaldehyde content < 0,1 % by weight*	No hazardous substances
Glass veils (AF; AG; AP; AT; AW; PA; S)	Formaldehyde under detection level*	
Grinding wheels	No hazardous substances	Phenol content < 1 % by weight Formaldehyde <0,1% Methanol <0,1% Methenamine <0,1 %

*Test method ISO 16000



Our products do not contain, in concentration above 0.1% in weight, any substances on the SVHC list (substances of very high concern) published by the ECHA on October 28th, 2008 or in the last up-date.

4 - FIRST AID MEASURES

General information: No specific measures required.

After excessive inhalation: Supply fresh air; consult a doctor in case of complaints once exposed to dusty environment.

After skin contact: In case of exposure to dust and consequent irritation immediately wash with water and soap and rinse thoroughly. Do not rub or scratch affected areas. If skin irritation continues, consult a doctor.

After eye contact: Once a dust particle enters into eyes, rinse opened eye for several minutes under running water and consult a doctor if necessary. Do not rub.

5 - FIRE FIGHTING MEASURES

In case of fire, glass filaments are not flammable, are incombustible and don't support combustion.

Only the packaging (plastic film, paper, cardboard, wood) and the small amounts of size or binder/PVC coating are combustible and could release some hazardous gases.

Above 300° C Polyester filaments may release: toxic and flammable gases, carbon monoxide. The generation of cleavage and oxidation products is subject to fire conditions. Non burned residues and contaminated water after firefighting should be disposed of in compliance with official regulations. Molten material should not be allowed to be in contact with the skin to which it can adhere and cause burns

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment:

Do not inhale combustion gases.

Wear fully protective suit including the SCBA (Self-Contained Breathing Apparatus)

6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION:

Just in case of dusty environment, avoid contact with the skin and the eyes. See chapter 8 for other instructions.

ENVIRONMENTAL PROTECTION:

No special measures required – all sorts of glass or polyester wastes are considered as **Inert Industrial Wastes**, or **Common Industrial Wastes** except for glass filament impregnated weaves for the abrasive industry (Grinding Wheels) which may be classified as Hazardous waste depending on local legislative standards.

April 2020

5/9



ADFORS

18, avenue d'Alsace- Les Miroirs – 92400 Courbevoie • France • Tel +33 (0)1 47 62 37 00 • www.adfors.com
S.A.S au capital de 34 400.000€ 402 976 161 RCS Chambéry

CLEANING:

Vacuum clean, sweep or shovel into containers normally used for glass or polyester filament waste (selective collection).

7 - HANDLING & STORAGE

HANDLING:

It is preferable to avoid prolonged contact with the skin: wear the protective equipment as indicated in the chapter 8.

Prevent and minimize the dust formation during the processing of products.

Provide local exhaust ventilation (LEV) if dust is formed on the processing machinery.

STORAGE:

Technical measures: Respect the stacking procedure recommended for each type of product.

Storage conditions: Store away from excessive humidity to prevent damage to the product and to the packing materials which could lead to storage safety problems.

Store in a well ventilated area and keep away from direct sunbeam.

8 - EXPOSURE CONTROL – PERSONAL PROTECTION

Ingredients with limit values that require monitoring at the workplace:

Continuous glass filaments are not respirable however certain mechanical processes might generate airborne dust or filaments (see chapter 11). Air monitoring could then be conducted to check the compliance to exposure limits applicable to generic dust or dust with no specific toxicity.

In case of grinding wheels and glass veils a low amount of the chemical substances stated in the chapter “3 – Composition” may be released from the products depending on handling and process applications. Especially if the product is heated-up or stored in closed and poorly ventilated areas an exposure monitoring should be conducted.

Engineering controls:

Provide local exhaust and/or general ventilation system to maintain low exposure levels.

Personal protective equipment:

Respiratory protection:

During operations releasing high quantities of dust, wear minimum FP1 or preferably FP2 EEC approved dust masks. In case of non-compliance to exposure limits of chemical substances as mentioned in the chapter “3-Composition” relevant cartridges must be used.

Protection of hands and other exposed parts of the body:

Gloves for the hands, long-sleeved garments and long leggings to prevent irritation. People with delicate skin should apply barrier cream to exposed skin areas.

Eye protection: safety goggles (or masks) or safety glasses.

9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	solid
FORM:	Rolls or strips of coated fabrics, veils, wheels cut of fibreglass grid, fibreglass mesh
COLOUR:	White or yellowish white, yellow, black, grey
ODOUR:	By opening the packages some smell of phenol or methanol may arise (grinding wheels)
SOFTENING POINT:	appr. 850 °C (E glass) and 690 °C (C glass)
MELTING POINT:	Not applicable.
DECOMPOSITION TEMPERATURE:	Size and binder/coating products start to decompose at 200°C PET fibre > 380° C
FLASH POINT:	none
EXPLOSIVE PROPERTIES:	none
DENSITY:	2.6 g / cu. cm (molten glass) 1,15 - 1,45 g/cm ³ (PET)
SOLUBILITY:	Very low solubility in water. Sizes and impregnating resins can be partially (and even totally) dissolved in most organic solvents.

10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY

Stable in normal use and storage conditions, and in normally foreseeable usage conditions. As already identified, some substances may be released during hot processes or storage.

HAZARDOUS REACTIONS

No chemical hazardous reaction is foreseeable.

HAZARDOUS DECOMPOSITION PRODUCTS

See Chapter 5 for hazardous decomposition products during fire.

11 - TOXICOLOGICAL INFORMATION

11.1 Glass filaments

ACUTE TOXICITY: not relevant

LOCALISED EFFECTS: **possible temporary irritations**

April 2020

7/9

This irritation is of a purely mechanical and temporary nature. It disappears when exposure is ended. It can affect the skin, the eyes and the upper respiratory tracts. This mechanical irritation is not considered to be a health hazard within the terms of Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures as Continuous filament glass fibres are not classified under this regulation. There is no need to use an Xi (irritant) label.

SENSITISATION: some **allergies** to continuous glass filaments have been declared.

LONG TERM TOXICITY:

Continuous glass filaments are not respirable according to the World Health Organisation (WHO) definition.

Respirable fibers have a diameter (d) smaller than $3\mu\text{m}$, a length (l) larger than $5\mu\text{m}$ and a l/d ratio larger than or equal to 3.

Fibers with diameters greater than $3\mu\text{m}$, which is the case for continuous filament glass fibre, do not reach the lower respiratory tract and therefore have no possibility of causing serious pulmonary disease.

Regulatory situation:

Following the IARC conclusion, **glass filaments are not classified as to their carcinogenicity**. They belong to the **Group 3 of IARC**. This classification has been confirmed by the IARC Working Group during his meeting of October 2001 and in the latest issue of the IARC monographs on the evaluation of carcinogenic risks to humans, volume 81 on Man-made vitreous fibres, published in 2002.

The International Labour Office (ILO) and the CSIP (Chemical Safety International Program) came to the same conclusions in a congress held in 1987.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures does not classified continuous glass filaments as having carcinogenic risks.

OSHA (Occupational Safety and Health Administration) and NTP (U.S. National Toxicology Program), official American organisations, have not listed glass filaments products as hazardous substances and the ACGIH (American Conference of Governmental Industrial Hygienists) has classified them as A4 (not classified as carcinogenic for Man). They are not concerned by the Canadian Controlled Products regulations (CPR).

MUTAGENIC RISKS, TERATOGENIC RISKS, RISKS FOR REPRODUCTION: no known risks.

11 .2 - Other components of binders and coatings

Certain substances being a part of components for applicate binders and coatings as specified in the chapter "3 – Composition" have specific toxicity. See relevant documents and standards for further information on their regulatory classification and scientific evaluation.

12 - ECOTOXICOLOGICAL INFORMATION

The products are not expected to cause harm to animals, plants nor fish.

13 – DISPOSAL CONSIDERATION

Depending on local regulations, glass filament and polyester wastes can either be considered as **inert waste**, **special non dangerous waste** or as **common industrial waste** except for glass filament impregnated weaves for the abrasive industry (Grinding Wheels) which may be classified as Hazardous waste depending on local legislative standards. As such they can be buried in landfills approved for these categories.

14 – TRANSPORT INFORMATION

INTERNATIONAL REGULATIONS:

Glass filament and polyester products are not considered as hazardous goods by transport regulations (IMDG, ADR/RID, ICAO/ IATA, DOT, TDG, MEX).

15 - REGULATORY INFORMATION

Continuous glass filaments and polyester products do not require hazardous product labelling (see Chapter 11).

Continuous glass filament, polyester filaments and polyester/glass staple fibres products are articles and for this reason they have not to be listed in most of the countries, for instance in the list EINECS in Europe, ELINCS, TSCA for the USA, DSL and NDSL for Canada, CSCL for Japan, AICS for Australia, PICCS for Philippine, KECL for South Korea, etc.

16 - OTHER INFORMATION

The information given by this document is based on the best knowledge at the date shown. Furthermore, users´ attention is drawn to the possible risks run when the product is used for any purpose other than the one for which it was designed.